



Product Data Sheet

CF40 Cryo-Compact Circulator

[Print Data Sheet](#)

Product Image



Order Information

Model: CF40
Order no.: 9400340

Available mains power:
230V / 50Hz
230V / 60Hz
115V / 60Hz

Downloads

+ [EasyTemp Software](#)

Similar Models

These models could also be interesting for you:

CF30
CF31
CF41

Sales & Support:

+49 7823 51-190

Monday to Friday
7:30 am - 17:00 pm

JULABO Labortechnik GmbH
Eisenbahnstrasse 45
77960 Seelbach/Germany
Phone +49 7823 51-0
Fax +49 7823 2491
info@julabo.de
www.julabo.de

Technical changes reserved.
Pictures may differ from original.

Description

Cryo-Compact Circulator for internal and external temperature applications

The new CF series offers compact refrigerated/heating circulators. With small overall dimensions the units can even be placed on a very small surface or within a complex installation. All models offer a heating capacity of 2 kW and classification 3 according to DIN12876-1. The maximum ambient temperature of +40°C as well as a ventilation air cooling allow installing the units very closely side by side with other units or directly under a fume hood. Furthermore all the models feature pump connections for external temperature applications and a bath opening for temperature control of small objects directly in the circulator bath. Wetted parts are made of high quality stainless steel or plastic. The instruments provide a reliable Microprocessor electronics with high temperature stability as well as warning and safety functions.

Advantages

- o Ergonomic design and easy operation
- o Small overall dimensions for lowest space requirement
- o Splash-proof keypad
- o Large, bright LED temperature display
- o Precise PID temperature control
- o RS232 interface for PC connection
- o Adjustable high temperature cut-off
- o Classification 3 according to DIN12876-1
- o Pump connections for external temperature applications
- o Bath opening for temperature control of small objects in the bath
- o Front drain

Technical Specifications

Working temperature range	-40 ... 150 °C
Temperature control	PID
Temperature stability	±0.03 °C
Display	LED
Display resolution	0.1 °C
Integrated programmer	not available
Heater capacity	2000 W
Cooling capacity	20 0 -20 -30 °C 470 400 280 120 W
Refrigerant	R404a
Pump capacity	Pressure: 350 mbar Flow rate: 15 l/min
Digital interfaces	RS232
Bath opening / bath depth (W x L / D)	19 x 3 / 19 cm
Filling volume	5.5 Liters
Dimensions (W x L x H)	28 x 46 x 46 cm
Weight	41 kg
Ambient temperature	5...40 °C
Classification according to DIN 12876-1	3 (FL)

Miscellaneous

Included: 2 each barbed fittings for tubing 8 and 12 mm inner dia. (pump connections M16x1 female)

Distributed by:



Carl Stuart Limited

ADVANCED APPLIED TECHNOLOGIES

Contact Us:

Ir Ph: 01 4523432

UK Ph: 08452 30 40 30

Web: www.carlstuart.com

Email: info@carlstuart.com