

EXO3

THE RIGHT SONDE AT THE RIGHT PRICE

Distributed by:



Tallaght Business Park Whitestown, Dublin 24, Ireland **D24 RFK3**

Tel: (01) 4523432 Fax: (01) 4523967

E-mail: info@labunlimited.com E-mail: info@labunlimited.co.uk Web: www.labunlimited.com

Quatro House, Frimley Road,

Camberley, **United Kingdom GU16 7ER**

Tel: 08452 30 40 30 Fax: 08452 30 50 30

Web: www.labunlimited.co.uk







The right sonde at the right price!

The parameters you need, without the features you don't.

Offering the greatest value of any sonde available in the market, EXO3 combines the maneuverability of EXO1 with the powerful antifouling wiper of the EXO2.

EXO3 is a purpose-built sonde for monitoring major water quality parameters, including: pH, conductivity, temperature, turbidity and dissolved oxygen.

But that's just the beginning of the great benefits EXO3 has to offer:



The best-priced, highestquality sonde for baseline water quality monitoring.



Flexibility to switch from continuous monitoring to spot sampling with a lighter, shorter form factor.



Integral SDI-12 communications makes it ideal for existing data collection platforms and installations, including stations that need easy replacement of our legacy 6-Series sondes.



Plug-and-play design with all existing EXO platform smart sensors, including Total Algae, fDOM, and Wiped Conductivity & Temperature.



The best antifouling wiper in the industry, protecting your sensors for up to **90 days** in the harshest conditions.



5-ports Available (4) sensors and (1) anti-fouling wiper

SPECIFICATIONS #E119



	<u> </u>	6		
	EXO1	EXO2	EXO2 ^s	EXO3
Available Sensor Ports	4	7	7	5
Battery Life	90 days*	90 days*	N/A	60 days*
Length	64.77 cm (25.50 in)	71.1 cm (28.00 in)	47.00 cm (18.5 in)	58.67 cm (23.1 in)
Weight	1.42 kg (3.15 lb)	3.60 kg (7.90 lb)	1.1 kg (2.43 lb)	2.0 kg (4.41 lb)
SDI-12 Communications	with Adapter	with Adapter	with Adapter	Integral
Vented Level		✓		
Antifouling Protection		✓	✓	✓
Auxiliary Expansion Port	\checkmark	✓	✓	

^{*}Battery life will depend on the type of sensors and measurement frequency.

EXO Smart Sensor Suite

Ammonium • Barometer • Blue-Green Algae (PC & PE) • Chloride • Chlorophyll • Conductivity • Depth Optical Dissolved Oxygen • fDOM • Nitrate • ORP • pH • Salinity • Temperature • Turbidity









"I'm very proud of the great work our customers do using our best-in-class sonde platform."

Supher a. Suil

Dr. Stephanie A. Smith EXO Product Manager



YSI.com/EXO







EXO2^s









EXO3 Specifications

5 sensor ports (4 ports available when central wiper in use) **Ports** Peripheral ports: 1 power communication port

Size Diameter: 7.62 cm (3.00 in) Length: 58.67 cm (23.1 in)

2.00 kg (4.41 lbs) with a full payload of 4 probes, 1 wiper, and probe guard installed Weight

Operating Temperature -5 to 50 °C (23 to 122 °F)

Storage Temperature -20 to 80 °C (-4 to 176 °F). Exception: 0 to 60 °C (32 to 140 °F) for pH and pH/ORP sensors

Depth Rating 0 to 250 m (0 to 820 ft)

Sonde: Bluetooth wireless technology, USB, RS-485, and integral SDI-12 Communications

Output Options with Adapters: USB, RS-232, or Modbus

Sample Rate Up to 4 Hz

Data Memory 512 MB total memory; >1,000,000 logged readings

Ordering Information

599503-00 EXO3 Sonde with no depth sensor 599503-01 EXO3 Sonde with 10m depth sensor 599503-02 EXO3 Sonde with 100m depth sensor 599503-03 EXO3 Sonde with 250m depth sensor

Distributed by:



Tallaght Business Park Whitestown, Dublin 24, Ireland D24 RFK3

Tel: (01) 4523432 Fax: (01) 4523967 E-mail: info@labunlimited.com E-mail: info@labunlimited.co.uk Web: www.labunlimited.com Web: www.labunlimited.co.uk

Quatro House, Frimley Road, Camberley, United Kingdom

Tel: 08452 30 40 30 Fax: 08452 30 50 30

GU16 7ER

