

PRESTO W91tt

Powerful Temperature Control Systems for demanding applications with a temperature range from -91 °C to +250 °C

The PRESTO W91 Highly Dynamic Temperature Control Systems are amongst the most powerful units available. Their impressive power is harnessed by cutting-edge control technology. The W91 provides extraordinary heating, cooling, and pumping performance. But it also comes with the functions and features that make the new generation of PRESTO so unique.

Your advantages

- Extremely fast cool-down and heat-up times
- Wide working temperature range without changing the bath fluid
- Very fast compensation of exothermic and endothermic reactions
- Unsurpassed power and efficiency
- Heating capacity up to 36 kW
- Ambient temperature range +5 °C to +40 °C
- Space optimized design creates more room directly next to the units
- Integrated 5.7" industrial color touchscreen displays all essential information and enables simple fingertip control
- Extensive warning, protection, and monitoring functions with detailed self-explanatory messages
- ICC cascade control for extraordinary precision, temperature stability ± 0.05 °C ... ± 0.2 °C
- Integrated programmer with real-time clock
- Filling level indicator and pump capacity displayed electronically
- Powerful circulating pumps, electronically adjustable in stages or by setting the pressure value
- Interface for SD memory card
- Connections for USB, Ethernet, RS232, and Alarm output
- Optional analog connections, RS485, Profibus DP, Modbus



Technical Data

Order No.	9421912.TT								
Category	Temperature Control PRESTO								
Working temperature range (°C)	-91 ... +250								
Temperature control	ICC								
Temperature stability (°C)	± 0.05 ... ± 0.2								
Setting / display resolution	0.01 °C								
Temperature Display	TFT Touchscreen								
Heating capacity (kW)	36								
Cooling capacity (Medium Ethanol)	°C	200	100	20	0	-20	-40	-60	-80
	kW	11	11	11	10	9.5	9	6.5	1.5
Pump capacity flow rate (l/min)	26 ... 80								
Pump capacity flow pressure (bar)	0.5 ... 3.0								
Pump connections	M38x1.5								
Refrigerant	R23, R404A								

External Pt100 sensor connection	integrated
Digital interface	RS232, SD memory card, USB, Ethernet, Modbus, Alarm-out Optional: Profibus
Ambient temperature	5 ... 40 °C
Dimensions W x L x H (cm)	95 x 127 x 190
Weight (kg)	790
Sound pressure level (distance 1 m) max. (dBA)	74
Viscosity max. (cSt)	50
Process volume min. (active heat exchanger volume) liters	28 (16)
Internal usable expansion vol. (liters)	40
Classification according to DIN12876-1	Classification III (FL)
Analog connection input / output	Optional
Cooling of compressor	2-stage Water
Cooling water connection	G ¾" male with barbed fittings for tubing ½" ID
Cooling water consumption (l/min)	16...43
Cooling water differential pressure (bar)	0.5
Available voltage versions	400V/3PNPE/50Hz 480V/3PPE/60Hz

All data refers to the nominal voltage of 400 V, 3-phase, nominal frequency of 50 Hz and ambient temperature of +20 °C. Cooling capacity measured at max. pump stage. All pump data refers to a bath fluid with a specific density of 1 kg/dm³.

Characteristics

Display



State-of-the-art display technology

TFT Display for comfortable user guidance, colored display of measurement values, graphs and control options, user-defined views



Convenience for several users

Administrator level for customizing instrument settings, user levels with limited permissions for fast and safe defined access, password protection, all levels adjustable



Control from the external application

External Pt100 sensor connection for precise measurement and control directly in the external application



Highest measuring accuracy

'Absolute Temperature Calibration' for manual compensation of a temperature difference, 3-point calibration

Operation



Optimal ease of use

Touch screen for direct operation via display

Temperature Control



For perfect results

'Intelligent Cascade Control', automatic & self optimizing adjustment of PID control parameters, temperature stability ±0.01 °C ... <±0.2 °C

Refrigeration Technology



Consistent cooling capacity

Easily removable venting grid for quick and easy cleaning



Instructions inside

Help menus and explanations in plain text for all control options, help messages and warning messages



Full control

'Temperature Control Features', for individual optimization, access to all important control parameters, additional settings for band limit, limits, co-speedfactor etc.



100 % Cooling capacity

'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Multilingual user guidance

Language selection for display of control options, notifications and warning messages via touchscreen



Energy saving cooling

Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines



Quiet as a whisper

Efficient components produce only a minimal sound decibel level



Quick support

If an error occurs, the integrated Black-Box function permits fast diagnosis by the JULABO service team



Space-saving footprint

All connections as well supply and exhaust air are located at the front or rear, no venting grids on the sides, units can be placed close to each other or the application

Technical Features



Intelligent pump system

Reliable and consistent pump capacity, electronically adjustable pump stages or pressure value, automatic adjustment of pump capacity to viscosity



Continuous operation up to +40 °C

Robust temperature control instrument, continuous operation even at ambient temperatures of up to +40 °C



Communication via networks

For the remote control of instruments via Ethernet networks, full access to all functions of the unit via a networkcapable PC



Easy transport by one person

Ergonomic design facilitates moving and positioning by one person



Intelligent communication

USB connection for data exchange (e.g. service data) or for wireless remote control via WirelessTEMP®



Filling level at a glance

Backlit indicator for selected pump stages and filling volume



Data exchange via SD-Card

For data exchange (e.g. service data) via SD memory card



Early warning system for high/low temperature limits

Maximum safety for applications, optical and audible signal when limits are exceeded.



Connections according to standard

RS232/RS485 dual-interface for serial data transmission according to EIA-485 industry standard (2-wire bus technology), upgradable with Profibus DP



Duplicate safety

Adjustable high temperature cut-off for internal tank and for integrated expansion vessel



Comfortable program control

Integrated programmer for the execution of time and temperature dependant profiles, 8 temperature profiles with 60 steps max., with real time clock



For flammable bath fluid

Classification III (FL) according to DIN 12876-1

Warning & Safety Functions

Distributed by:

Lab Unlimited
CARL STUART GROUP

Tallaght Business Park
Whitestown, Dublin 24,
Ireland
D24 RFK3

Tel: (01) 4523432
Fax: (01) 4523967
E-mail: info@labunlimited.com
Web: www.labunlimited.com

Quatro House, Frimley Road,
Camberley,
United Kingdom
GU16 7ER

Tel: 08452 30 40 30
Fax: 08452 30 50 30
E-mail: info@labunlimited.co.uk
Web: www.labunlimited.co.uk