



Parameters: Dissolved Oxygen % and ppm (electrochemical) Temperature BOD (biochemical oxygen demand)

#### The EcoSense DO 200A is also available as a kit with a 1-, 4- or 10- meter cable.



## **EcoSense DO200A Dissolved Oxygen/Temperature**

### Accurate, economical, handheld measurements

The EcoSense® line of compact, handheld instruments provides the most accurate data in the most affordable format. The instruments feature an easy-to-use interface, one-hand operation, IP67 waterproof case, and low cost of ownership over the life of the product. The DO200A simultaneously measures dissolved oxygen (% air saturation and ppm) and temperature with the following features:

- IP67 Waterproof housing
- Automatic temperature compensation
- 1-year instrument warranty
- 4- and 10-meter field cables available or lab self-stirring BOD probe
- Manual input for salinity and pressure compensation
- Low battery indicator with 500 hour battery life
- Screw-on cap membranes with low stirring and fast response
- Auto shutoff function after 30 minutes of inactivity
- 50 data set memory

The DO200A is designed for quick, accurate results in an economical platform. The ability to measure DO and temperature in a simple, compact handheld allows the instrument to be used across multiple application sampling strategies from the field to the lab with the optional BOD probe. With a one-year instrument and electrode warranty, waterproof case and ease-of-use, the EcoSense DO200A will fit your needs.





Tallaght Business Park Whitestown Dublin 24 Ireland

Tel: (01) 4523432 Fax: (01) 4523967

Web: www.labunlimited.com Web: www.labunlimited.co.uk

Unit 59, Frimley House 35 High Street Frimley, Surrey **GU16 7JQ** 

Tel: 08452 30 40 30 Fax: 08452 30 50 30 E-mail: info@labunlimited.com E-mail: info@labunlimited.co.uk

# DO200A System Specifications (Instrument, Probe, and Cable)

Temperature Range -6 to 46°C (21.2 to 114.8°F)

Resolution  $0.1^{\circ}$ C Accuracy  $\pm 0.3^{\circ}$ C  $\pm 1$  digit

Dissolved Oxygen % Saturation Range 0 to 200%

Resolution 0.1% air saturation

Accuracy  $\pm 2\%$  of the reading or  $\pm 2\%$  air saturation, whichever is greater

Dissolved Oxygen ppm (mg/L) Range 0 to 20 ppm
Resolution 0.01 ppm

Accuracy  $\pm 2\%$  of the reading or  $\pm 0.2$  ppm, whichever is greater

## DO200A Additional Specifications

#### Operating range

Temperature 0° to 50° C (32 to 122°F)

Relative Humidity up to 95%

Water rating IP67 waterproof

Size 78 mm wide (widest point) x 184 mm long x 37 mm deep (3.1 in. x 7.25 in. x 1.45 in.)

Weight with battery 272 grams (0.6 lb.) ATC Probe Thermistor,  $10k\Omega/25^{\circ}$  C

Battery One 9 volt included with purchase; 500 hour battery life

Salinity compensation 0.0 to 40.0 ppt (manual input during calibration)

Pressure compensation 600 to 1100 millibar (450 to 825 mmHg) (manual input during calibration)

Calibration back-up Yes

Audio feedback Yes, all keys

Memory 50 data set reviewable memory

Auto shutoff Automatically powers off after 30 minutes of inactivity

### DO200A Ordering Information (order items separately or as a kit)

D0200A D0200A Dissolved oxygen and temperature instrument only
D0200ACC-01 D0200A instrument, 1-meter cable and probe, hard-sided carrying case kit
D0200ACC-04 D0200A instrument, 4-meter cable and probe, hard-sided carrying case kit
D0200ACC-10 D0200A instrument, 10-meter cable and probe, hard-sided carrying case kit
200-1 1-meter dissolved oxygen and temp field cable and probe only
200-4 4-meter dissolved oxygen and temp field cable and probe only
200-10 10-meter dissolved oxygen and temp field cable and probe only

200-BOD Stirring BOD probe, 115V, 1.5-m cable 200-BOD-230V Stirring BOB probe, 230V, 1.5-m cable

606036 Hard-sided, plastic carrying case with form fitted foam insert; 31.75 x 22.86 x 9.4 cm (12.5 x 9 x 3.7 in)

5908 Cap membrane kit, 1.25 mil PE with electrolyte solution, 6 each (yellow cap)

Distributed by:



Tallaght Business Park
Whitestown
Unit 59, Frimley House
35 High Street
Publin 24
Frimley, Surrey
Ireland
GU16 7JQ

Tel: (01) 4523432 Tel: 08452 30 40 30 Fax: (01) 4523967 Fax: 08452 30 50 30

E-mail: info@labunlimited.co.uk
Web: www.labunlimited.com
Web: www.labunlimited.co.uk

